

CLAIMS

✓ 1. (presently amended) A blister packaging unit (10) in which at least two different components are retained captive, at least one of which has a pulverulent or granular consistency and is to be prepared before use with the further packaged component(s) in a mixer or applicator to form a ready-for-use mixture, whereby the components are inserted in appropriately preshaped receptacles (32; 34) in ^{packaging unit} ~~the a blister~~ (30) of a suitable film ~~or other material~~, and the ~~latter blister is being~~ closed on the ~~a side~~ of the ~~an~~ open mouth of the receptacles by a cover (36) ~~of cardboard, plastic, metal or some other suitable material which may be torn off or opened in some other mannerto allow access to the component(s), wherein the~~ different components are packed separated from one another in separate individual packages, of which the component(s) having the pulverulent or granular consistency is/are packaged in an individual blister package (12; 14; 16) which is shaped at least approximately generally complementarily to ^{the an associated} ~~the an associated~~ receptacle (32) in the ^{packaging unit} ~~blister~~, ^a ~~the blister~~ ^{of the individual blister package having a} ~~of which has the shape of~~ an elongate trough element (12) of plastic tapered in the manner of a spout at at least one end, whereby the trough element(s) is closed by a separate tear-off cover (16) ~~of cardboard, plastic, metal or some other suitable material which may be torn off or opened in some other mannerto allow access to the component(s).~~

Sub D1
B1
2. (previously amended) The blister packaging unit as claimed in Claim 1, in which the components having a pulverulent or granular consistency is/are packaged in a sterile manner and the sterility must be guaranteed until preparation to form the ready-to-use mixture wherein both the material of the trough element (12) and the material of the separate cover (16) and their connection is constructed to be impermeable to the passage of germs.

3. (previously amended) The blister packaging unit as claimed in Claim 2, wherein the material of the trough element (12) and/or the separate cover (16) is constructed to be permeable to radiation with ionising beams for the purpose of radiation sterilisation of the component(s) having a pulverulent or granular consistency.

4. (presently amended) The blister packaging unit as claimed in claim 1, wherein the separate tear-off cover (16) is constructed to be permeable for gas treatment, ~~for instance with ethylene oxide,~~ for the purpose of sterilising the component(s) having a pulverulent or granular consistency.

5. (previously amended) Blister packaging unit as claimed in claim 1, wherein two separate covers (16) with different chemical, physical

properties are applied in two successive steps to the peripheral
flange (14) of the trough element (12).

507
D'